

LED Post Top Light

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 140 lm/W, Dimmable

FEATURES

Lumen Output	10000 to 21000 lumens
Efficacy	140 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3000K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

APPLICATIONS

Premium outdoor luminaire suitable for entrances, building exteriors, parks, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and 3-Wattage models. Operating temperatures -40°F to 113°F (-40°C to 45°C).

MOUNTING

Includes 3-inch Slip-Fit Pole Mounting base.

OPTICS

Anti-UV Clear Polycarbonate IES/ NEMA Type 5 Lens.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

Tunable 150W Max Models




TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3000K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: 3-Wattages (150W Max)

Power Factor: >0.9

Total Harmonic Distortion (THD): <10%

Operating Temperature: -40°F to 113°F (-40°C to 45°C)

LIGHTING DATA

Lumens: 4200 to 21000

Lumens Per Watt: 140 lm/W

Correlated Color Temperature (CCT): 3-CCT (30K, 40K, 50K)

Dimmable: 0-10V

Color Rendering Index (CRI): >70

L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
PT01-150W-H-T	(70W, 100W, 150W)	120-277V	0.64A@120V, 0.28A@277V 0.92A@120V, 0.40A@277V 1.38A@120V, 0.60A@277V	10000 14000 21000	140 lm/W	(3000K, 4000K, 5000K)	0-10V	Black	ø14.23"C x 9.23"H

PHYSICAL DIMENSIONS

All Models

ø14.23"C x 9.23"H

